

OFF-HIGHWAY TRAILER AXLES & SPECIALTY PRODUCTS

TIRE INFORMATION GUIDE

K-B Axle Co.

5775 NW WAGON WAY / HILLSBORO, OR 97124-8531 / ph: 866.531.0600 / fx: 503.531.0601

MODEL	Beam Capacity	Brake Size	Wheel or Hub Type	Rim Size	Tire Size	Tire O.D.	Loaded Radius
Wheels accepting demountable rims preferred for axle capacities of 40,000 lbs. and over.							
T40	40,000	20 X 8	10 stud 13 3/16 B.C.	H 8.50-24 8.50-25	P 12.00-24 P 12.00-25	49.6	23.3
S54	60,000	20 X 8	Wheel for Dual Demountable Rims	S 10.00-24 10.00-25	P 14.00-24 P 14.00-25	54.0	25.1
S55	60,000	20 X 8	10 stud 13 3/16 B.C.	H 10.00-24 10.00-25	P 14.00-24 P 14.00-25	54.0	25.1
S65	75,000	20 X 8	Wheel for Dual Demountable Rims	S 11.00-25 13.00-25	P 16.00-25 P 18.00-25	57.2 63.8	26.3 29.2

* This information varies with tire selected.

Tire and rim manufacturer's data must be verified for each application. Specifications are nominal only.

H=Hub

S=Spoke Wheel

P=Preferred Applications